

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our <u>Historical View FAQs</u> or contact our <u>Customer Service</u>.

Coatings, Fire Retardant

See General Information for Coatings, Fire Retardant

CONTEGO INTERNATIONAL INC R25382

PO BOX 49

ROCHESTER, IN 46975-0049 USA

HS Fire-retardant coating covering UL Certified, field spray applied foamed plastic, as described below, in accordance with manufacturer's application instructions. Certified in accordance with UL 1715 for use in wall constructions.

CERTIFIED FOR USE WITHOUT A THERMAL BARRIER IN ACCORDANCE WITH SECTION 2603.9 OF THE INTERNATIONAL BUILDING CODE WHEN INVESTIGATED TO ANSI/UL 1715.

Certification contingent on coating applied in accordance with manufacturer's application instructions at a coverage rate of 58 ft2/gal over UL Certified, Gaco Western, Polyfoam "A" Isocyanate Component and Polyfoam 2003 Resin Component, 2 in. thick, 2.0 pcf density, field spray applied foamed plastic, having a Flame Spread Index of 40 and Smoke Developed Index of 350-450.

Last Updated on 2017-03-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."